





THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO J.S.T. AND SHALL NOT BE USED OR ADAPTED, COPIED, OR PUBLISHED WITHOUT WRITTEN PERMISSION. IN THE EVENT THAT THERE ARISE ANY DOUBTS OR CONTROVERSIES BETWEEN JAPANESE AND ENGLISH EXPRESSION, THE JAPANESE TEXT SHALL PREVAIL.

1
2
3
4
5
6
7
8
A
B
C
D
E



推奨基板穴寸法 (コネクタ装着側)
Recommendable P.C.Board hole layout
(The figure viewed from connector mounting side.)

NOTE

- 1. 一般公差 : ± 0.3
- 2. 基板の穴ピッチの公差は累積しないこと。

NOTE

- 1. Unless otherwise specified, tolerance are ± 0.3
- 2. Tolerance of hole pitch on PCB are not cumulative.

極数 Circuits	寸法/Dimensions	
	A	B
9	10.0	15.0
15	17.5	22.5

2	コンタクト CONTACT	銅合金 COPPER ALLOOY	すずめっき TIN PLATED	殿
	ハウジング HOUSING	PA (GF強化) PA (GF)	赤 RED	
品番 No.	部品名 PART NAME	材質 MATERIAL	処理 SURFACE FINISH	備考 REMARKS
サイズ SIZE	単位 UNIT	投影法 PROJECTION	作図年月日 DATE	納入先 CUSTOMER
A3	METRIC		MAR.15.2024	品名 SERIES NAME
日本圧着端子製造株式会社 J.S.T. MFG.CO.,LTD.				JET コネクタ リセプタクル (強ロックタイプ) JET CONNECTOR RECEPTACLE (Secure lock type)
				形番 PART No.
				図番 DRAWING No.
				() R-JET-P (LF) (SN)
				KRD-33656-1 R0