

ä°§ ä“ □ é”€ ä”® ä □ ^ ä □ €

ä³⁄₄æ-¹ⁱ⁄₄^ä □-
ä‡°ä°ⁱ⁄₄%ⁱ⁄₄šé, ¢ä □ °æ¶||è □ ”æœ°æ¢°è®³⁄₄ä □ ‡æœ%œ™ □ ä...-ä □ , ä □ ^ä □ €¢ⁱ⁄₄-
ä □ ·ⁱ⁄₄š2015ä¹’01æœ^15æ—¥s

éœœæ-¹ⁱ⁄₄^ä¹°ä □ —ä°ⁱ⁄₄%ⁱ⁄₄š ¢-³⁄₄ä®šäœ°¢, ¹ⁱ⁄₄š
¢-³⁄₄ä®šæ—¶é—
¹ⁱ⁄₄š2015ä¹’01æœ^15æ
—¥

ä, °æ~Ž¢;®ä □ €æ-¹é’fä»»ⁱ⁄₄€¢;®ä, □ ä □ ^ä □ €é;°ä^©æ%§è;€ⁱ⁄₄€¢» □ ä □ €æ-
¹ä □ □ ä·†ⁱ⁄₄€è³⁄₄⁴æ^ □ ä‡, ä, <ä...±èⁱ⁄₄š

ä, €ä€ □ ä°šä“ □ ä □ □ ¢§°ä€ □ äž<ä □ ·ä€ □ æ•°é‡ □ ä€ □ ä³⁄₄>è’§æ—¶é—’ä □ Šæ•°é‡ □

æ ‡¢š,,¢%©ä □ □ ¢§°	è§,,æ ¹⁄₄äž< ä □ ·	æ• °é‡ □	ä □ • ä » . é ¢ □	æ € » é ‡ ‘ é ¢ □	ä°œ □ □ è’§æ—¶é— ’ä □ Šæ•°é‡ □ ä □ Šä □ ^ä □ €æ%§è; €æ □ ;ä»¶
BY4000ä □ €é³æ•°ä— ¢›, ä¹⁄₂ □ ä¹⁄₄ □ ä®%œè;”	RL1 9396 2	1	8 4 0 0	8 4 0 0	
ACDC- 3400INDé³ä¹⁄₂¢è;”	RL1 9396 3	1	6 0 0 0	6 0 0 0	

ACD-56 HPQé³á½çèj”	RL1 9396 4	1	6 6 0 0	6 6 0 0
ACDC- 100TRMé³á½çèj”	RL1 9396 5	1	3 6 0 0	3 6 0 0
MA410é³á½çèj”	RL1 9396 6	1	7 9 2 0	7 9 2 0
æ³”í/š				
â□^è@jé†‘éç□í¼šä°æ°‘â,□í¼^â□šâ†™í¼%í¼š32520daxieâ...fæ•’ã€,				

â°Œã€□è”é†□èj□æ±,ã€□æšŒæœ¯æ ‡â††ã€□ã³⁄⁄æ—

¹â¹è”é†□è‘Ÿè‘£çš,,æ□jã»¶â¹ŒæœŸŸé™í¼š

ä,‰ã€□ä°í¼^æ□□í¼%è‘šäœ°ç,¹ã€□æ—¹â¹⁄⁄□í¼šä¹⁄²“äœ°ç‰©æµ□

â»ã€□è¿¼“æ—¹â¹⁄⁄â□šâ^è³⁄⁄ç«™æ,¯â¹Œè¹ç””è‘Ÿæ<...í¼šä¹°â@¶æ‰¿æ<...

ä””ã€□âŒ...è£...æ ‡â††ã€□âŒ...è£...ç‰©çš,,ã³⁄⁄â””â,Zâ>žæ”¶í¼šæœ¯ç®±ç-‰

â...-ã€□èªŒæ”¶æ ‡â††ã€□æ—¹æ³•â□šæ□□â†°â¹⁄⁄,è®®æœŸŸé™í¼šä¹⁄²äœ°èªŒæ”¶

ä,fã€□èš□æœ°â□†â“□ã€□é...□ã»¶â·Ÿâ...æ•°é†□â□šã³⁄⁄â””âšžæ³•í¼šš□â°šâ“□â□,è‘š

â...«ã€□ç»“ç®—æ—¹â¹⁄⁄â□šæœŸŸé™í¼šé“¶èjŒè¹⁄²¬è¹¼Œæ¬³⁄⁄â^°â□‘è‘š

â¹□ã€□â¹,éœŒæ□□ã³⁄⁄æ<...ä¿¼í¼Œã□jç««â□^â□Œæ<...ä¿¼â¹¼Œã¹⁄²œä,°â□^â□Œé™,,ã»¶ã€,

â□□ã€□æ ‡çš,,ç‰©œ‰œæ‰œæ□fè†ªâ”æ,...â...æ¬³⁄⁄æ—¶è¹⁄²¬çš»í¼Œã¹⁄²†â¹°â□—

ä°œæœªâ±ŸèjŒæ”¯â»~â»·æ¬³⁄⁄ä¹°‰šjçš,,í¼Œæ ‡çš,,ç‰©â±žâ†°â□—ä°œ‰œæœ‰ã€,

ā□□ā,ēāē□ē;□ç°ē'fā»ī/4š

ā□□ā°ēāē□ēšfā†ā□ā□ēç° ç°·çš,,æ-ā¹/4□ç°±ā¹/2“ā°ā°ā»Žā,ā^—
ā,-ēç°æ<ā,ēçš□ī/4š

1āē□ā> ā±ē;ē(Eææ-ā□ā□ēā□'ç°Yā°°ē®®ā□□ā·†ēšfā†ā,□æ^□çš,,æ□□ā°æ°'ā°ā
»²ēf□āš°ā°ā¹/4šā»²ēf□āē,

2āē□ā> ā±ē;ē(Eææ-ā□ā□ēā□'ç°Yā°°ē®®ā□□ā·†ēšfā†ā,□æ^□çš,,ā³/4□æ³·ā□'ā°°
æ°'æ³·é™çèμ·è°°āē,

ā□□ā,%āē□ā...¶ā®fā°ē;¹è'æ~Žī/4š

ā ³ /4>æ-ī ¹ /4^ā□-ā [†] °ā°ī/4°āī/4šæ□°æ¶> ā□·ā ¹ /2□ā□□çš°ī/4šé,çā□°æ¶ è□°ææ°æç°è® ³ /4 ā□ [†] ææ°°é™□ā...-ā□, ā□·ā ¹ /2□āæ°ā□ēī/4šæ²āē—é,çā□° æ³·ā®šā»fè;°ā°ī/4šè□fçfš āš°æ°°~ā»fç□†ā°ī/4šæ□°æ¶> ç°μè°□ī/4š0319-8322210 ā ¹ /4ēæ^·è;ēī/4š è'ā□·ī/4š	éæēæ-ī ¹ /4^ā ¹ °ā□— ā°°ī/4°āī/4š ā□·ā ¹ /2□ā□□çš°ī/4 š ā□·ā ¹ /2□āæ°ā□ēī/4 š æ³·ā®šā»fè;°ā°ī/4š āš°æ°°~ā»fç□†ā°ī /4š ç°μè°□ī/4š ç°Žā□·ī/4š	ā...¬è°□æ- ī ¹ /4š ā...¬è°□æ,,□ èš□ī/4š ç»□āšžā°°ī/4š æ□°æ¶>
ç;®è®ā□Žè°·ā>žā ¹ /4 ī/4š	ā>žā ¹ /4 ā□·ç □ī/4š03 19-8322210	
	è□°ç³»ā°ī/4šæ□°æ¶> æ°°< ææ°ī/4š18714220826	

BY4000ā□ēé°æ°ā—ç>,ā¹/2□ā¹/4□ā®°è;°

ā°šā°□æ□□ē;°ī/4š

BY4000ǎ□CEé'æ•°ǎ—
ç),ǎ½□ǎ¼□ǎ®%œëĩ"æ~æ~ǎ...~ǎ□,ç²¼ǎ¼fç"ǎ"¶çš,,ǎ□~ǎ,€æ~¼ǎ,“ǎ,°çŽ°ǎœ°æµ«è~•çš,,ǎ□šǎŠŸèf¼ǎ»°èĩ~¼CEǎ...•æœ%œé«~ç²¼ǎ°¶ǎ€□é«~ç"ǎ®šǎ€□ǎ½ŽǎŠŸè€—ǎ€□ǎ½¼ç"æ—
¹ǎ¼¼ç-°œç%œ¹ç,¹ǎ€,ǎ□~ǎ»¥ǎœ"èé«æµ«ǎ»žè~ǎ,□ǎ¼€è~çš,,æf...ǎ†µǎ,ç)´æŽ¥æµ«é†□ǎ°æµ□ç"µǎŽ«ǎ'CEǎ°æµ□ç"µæµ□¼¼CEæµ«é†□ǎ,□ç"µǎŽ«è—´ǎ€□ǎ,□ç"µæµ□è—´ǎ'CEç"µǎŽ«ç"µæµ□è—´çš,,ç),ǎ½□¼¼CEæ-□ǎ□-¼¼CEè¼¼ǎ□~è—
´æŽ¥æµ«ǎ¼—
ç"µè~çš,,ǎŠŸçŽ¼ǎ»æ•°ǎ'CEǎŠŸçŽ¼¼¼CEǎ□~ǎ»¥ǎ~œǎ«ǎ,%œç),ç),ǎ°□¼¼CEǎ□~ǎŽ«ǎ™"æŽ¥ç°¼ç),ǎ~«ǎ€□æ,,Ÿæ€šǎ€□ǎ®¹æ€šç"µè~¼¼CEæµ«è~•ǎ°CEæ-¼ǎ»žè~ǎ'CEæ~□ǎ•®ǎ¼□æŠ□ç»ç»Ÿ¼¼CEè~»ǎ†°ǎ•®ǎŠ"ǎ¼□æŠ□ǎ□,,ç»,CTǎ¹è—
´çš,,ç),ǎ½□ǎ...³ç»¼¼CEæf€æŸŸç"µǎ°èĩ"çš,,æŽ¥ç°¼æ-Łç¼®ǎ,Žǎ□¼¼CEæf€ǎ¼®ç°¼è~è®¼ǎ□¼ç-°œǎ€,
BY4000ǎ□CEé'æ•°ǎ—
ç),ǎ½□ǎ¼□ǎ®%œëĩ"é††ç"™è¶...ǎ□šLCDæ~¼ç°ǎ±□¼¼CEǎ...•æœ%œè~□ǎ±□èfCEǎ...%œ¼¼CEæ~¼ç°ǎ,€ç)®ǎ°†ç,,¶¼¼CEǎ°¼æ~¼ç²¼ç¼Žè±ǎ□Žǎ□~èš,ǎ€,
BY4000ǎ□CEé'æ•°ǎ—ç),ǎ½□ǎ¼□ǎ®%œëĩ"é€,ç"™ǎŽç"µǎŠ»ǎ€□çŸ³æ²¹ǎCE—
ǎ•¥ǎ€□ǎ†¶é†•ǎ€□è~□è~ǎ€□æ°"è±;ǎ€□ǎ•ŸçŸ¼¼□ǎ,šǎ€□çš´ç"é™éæ;ǎ€□è®¼é†□éf—´ç-°œǎ€,

ACDC-3400INDé'ǎ½çèĩ"

ǎ°šǎ"□æ□□è¼°Ÿ¼š

Model: ACDC-3400 IND Clamp Meter¼¼CEACDC-3400 INDé'ǎ½çèĩ"

This CAT IV rated clamp is ideal for industrial applications and utilities that require an extra level of safety. Includes True RMS sensing for accuracy and dependability. Extra large jaw to accommodate wide diameter wires.

TRMS

Measures AC Current up to 1000 ACA, Voltage up to 750 VAC / 1000 VDC, Frequency, Resistance and Capacitance and Duty Cycle

1000A DC Current

Peak Hold

Relative Zero

Audible continuity

Auto and manual ranging

Auto power off

Data Hold

Backlight

Diode Test

Duty Cycle

Accommodates conductors up to 2" (51mm) in diameter

Safety CAT IV 600 V, CAT III 1000 V

Test leads, battery (installed), Users Manual, and Carrying Case included with the product

ACD-56 HPQé''á½çèì''

ã°§ä“□æ□□èç°¶%§

Model: ACD-56 HPQ Clamp-on meter, ACD-56 HPQé''á½çèì''

TRMS Measurements

AC Current up to 400A

AC/DC Voltage up to 600V

Active, Reactive and Apparent Power Single/Three Phase

Power Factor, Cos Ø Single/Three Phase/Energy

Frequency (with test leads and jaw)

Phase sequence with single wire (patented)

Resistance & Continuity

Autorange

Auto Power OFF

Backlight

Data Hold

MAX/MIN/AVG recording

Fast PEAK function (1ms)

Low battery indication

Voltage and Current Harmonics up to 25th with THD%

ACDC-100TRMé''á½çèì''

原创力文档

max.book118.com

预览与源文档一致, 下载高清无水印