



Click [here](#) for the 3D model.

## General Information

Series	SMD Mil DSCC03028
Style	SMD Chip
Description	SMT, MLCC, DSCC 03028
RoHS	No
Prop 65	<b>WARNING:</b> Cancer and reproductive harm - <a href="https://www.p65warnings.ca.gov/">https://www.p65warnings.ca.gov/</a>
Termination	Lead (SnPb)
Failure Rate	N/A
Testing and Reliability	Group C
Qualifications	DSCC 03028
AEC-Q200	No
Miscellaneous	Full Group C Testing.
Shelf Life	78 Weeks
MSL	1

## Dimensions

Chip Size	0603
L	1.6mm +/-0.15mm
W	0.81mm +/-0.15mm
T	0.91mm MAX
B	0.36mm +/-0.15mm

## Packaging Specifications

Packaging	T&R, 178mm, Plastic Tape
Packaging Quantity	4000

## Specifications

Capacitance	150 pF
Capacitance Tolerance	10%
Voltage DC	6.3 VDC
Dielectric Withstanding Voltage	15.75 VDC
Temperature Range	-55/+125°C
Temperature Coefficient	BR
Dissipation Factor	5%
Aging Rate	1% Loss/Decade Hour
Insulation Resistance	100 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.