

1

2

3

4

[ASSEMBLE TOOL]

APPLICABLE OUTER CONDUCTOR CRIMPING TOOL

:HT303/UM.MSS-T-1(2.5 HOLE)

10 ATTACHED

1/2-28UNEF-2A

1

4 PRESS FITTING, ATTACHED

3 PRESS FITTING

2

8 ATTACHED

9 ATTACHED

5 ATTACHED

6 ATTACHED

7 ATTACHED

RECOMMENDED PANEL CUTOUT
(PANEL THICKNESS : 1~2 mm)

RoHS COMPLIANT

5	PTFE		10	POLYOLEFIN	HEAT SHRINK TUBING(BLACK)
4	BERYLLIUM COPPER	GOLD PLATING	9	STEEL	NICKEL PLATING
3	BRASS	NICKEL PLATING	8	BRASS	NICKEL PLATING
2	PTFE		7	BRASS	NICKEL PLATING
1	BRASS	NICKEL PLATING	6	BRASS	NICKEL PLATING

NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
-----	----------	------------------	-----	----------	------------------

UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
-------------	--	----------------	-----------	--------------------------	----------	---------	------

HRS	HIROSE ELECTRIC CO., LTD.	APPROVED : MH. YAMANE	11. 01. 24	DRAWING NO.	EDC4-131200-40		
		CHECKED : TS. NOBE	11. 01. 21	PART NO.	BNC(75)-BPJ-1.5CV-(P)(40)		
		DESIGNED : YI. FUNADA	11. 01. 18	CODE NO.	CL302-0369-8-40		
		DRAWN : YI. FUNADA	11. 01. 18				

FORM HC0011-5-51

2

3

4

4