

Sep.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

1		2		3		4	
A						A	
B						B	
C						C	
D						D	
E						E	
F						F	

17.5 ± 0.3
12.7 ± 0.1
12.7 ± 0.1
17.5 ± 0.3
4 × Ø 3 ± 0.1
(12)
Ø 6
6 Attached
15.8 ± 0.3
2.3 ± 0.2
(3.9)
Ø 1.6 ± 0.1
Ø 5.8 ± 0.1
Ø 9.5 ± 0.2
Prick punch (4 Points)
2 Attached
3 Attached
4 Attached
5 Attached
6 Attached

3	PHOSPHOR BRONZE	GOLD PLATING	6	POLYOLEFIN	HEAT SHRINK TUBING
2	PTFE		5	BRASS	GOLD PLATING
1	BRASS	NICKEL PLATING	4	PTFE	
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS

UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
		HIROSE ELECTRIC CO., LTD.		APPROVED : NK. NINOMIYA 20211115 CHECKED : NK. NINOMIYA 20211115 DESIGNED : MT. KANEKO 20211112 DRAWN : NK. OOSHIMA 20211112	DRAWING NO. EDC-315323-00-00 PART NO. BNC-PJ-DFS111-A CODE NO. CL0302-0416-6-00			 1/1

FORM HC0011-5-51