

A
B
C
D
E

8 $\begin{array}{c} +0.04 \\ -0.13 \end{array}$ HEX

Diagram of a vertical rectangular plate with a central vertical slot. The plate has a height of 12 and a width of 5. A callout points to the right edge of the plate, labeled "12 Attached".

Technical drawing of a mechanical assembly with 11 numbered callouts. The drawing shows a cross-section of a bolted joint. Callout 1 points to the hexagonal nut. Callout 2 points to the base plate. Callout 3 points to the bolt head. Callout 4 points to the bolt shank. Callout 5 points to the bolt threads. Callout 6 points to the bolt head. Callout 7 points to the base plate. Callout 8 points to the bolt head. Callout 9 points to the bolt shank. Callout 10 points to the bolt threads. Callout 11 points to the bolt head. The drawing includes dimensions: a total height of 28.1, a width across flats of $9^{+0.05}_{-0.15}$, a bolt diameter of $\varnothing 4.1$, and a base plate diameter of $\varnothing 14.5 \pm 0.5$. A label "Attached" is next to callout 11.

6	SILICONE RUBBER		12	POLYOLEFIN	HEAT SHRINK TUBING (BLACK)
5	BRASS	SILVER PLATING	11	COPPER	NICKEL PLATING
4	BERYLLIUM COPPER	SILVER PLATING	10	BRASS	GOLD PLATING
3	BRASS	NICKEL PLATING	9	PTFE	
2	PTFE		8	BRASS	NICKEL PLATING
1	BRASS	NICKEL PLATING	7	BRASS	NICKEL PLATING
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS

UNITS mm		SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.	APPROVED : NK. NINOMIYA		20211108	DRAWING NO.	EDC-029284-41-00			
	CHECKED : NK. NINOMIYA		20211108	PART NO.	BNC-P-1. 5WCR(41)			
	DESIGNED : MT. KANEKO		20211105	CODE NO.	CL0302-0295-3-41			
	DRAWN : YK. MITSUISHI		20211105	 				