Sep.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE



NOTES
1. WHEN MATING A PLUG CONNECTOR, PLEASE HOLD MILLING AREA OF 5.8±0.2 WITH A SPANNER NOT TO PLACE STRESS ON PCB BY THE TORQUE.
2. 0-80UNF-2B SCREW TIGHTENING TORQUE IS 0.09N・m.
3. PLEASE USE SCREWS WITH LENGTH OF L WHEN MOUNTING, WHERE L = PCB THICKNESS t1 + SPRING WASHER THICKNESS t2 + 2mm.
4. RESIST IS PROHIBITED INSIDE THIS AREA.
4. 5. THIS PRODUCT IS A SOLDERLESS CONNECTOR FOR PROTOTYPE EVALUATION OF HIGH SPEED TRANSMISSION BOARDS. IT IS NOT RECOMMENDED FOR USE IN ACTUAL COMMERCIAL EQUIPMENT.
6. PCB THICKNESS t1 SHOULD NOT BE LESS THAN 1mm.
7. TRACE PATTERN DEPENDS ALSO ON ELECTRIC CONSTANT, THICKNESS AND LAYER CONSTRACTION OF PCB. FOR BETTER RF PERFORMANCE, EM SIMULATION OF PCB WITH CONNECTOR IS RECOMMENDED.

ROHS COMPLIANT

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
3	PTFE				
2	BERYLLIUM COPPER	GOLD PLATING	5	PEI	
1	STAINLESS STEEL	GOLD PLATING	4	STAINLESS STEEL	PASSIVATED

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm/inch	5 : 1	4	1	DIS-D-00016641	TS. KANEKO	TS. NAKAGAWA	20230824

HIROSE ELECTRIC CO., LTD.

APPROVED	TS. NOBE	20180822	DRAWING NO. EDC-374263-00-00
CHECKED	HA. NISHIMURA	20180822	PART NO. H2.4-R-SR2-S
DESIGNED	MH. OGUSU	20180822	CODE NO. CL0338-0605-0-00
DRAWN	MH. OGUSU	20180822	4 1/1

FORM HC0011-5-51