molex

Part Number: 39000089

Product Description: Mini-Fit Female Crimp Terminal, Gold (Au) over Brass, 16 AWG, Reel

Series Number: 5556

Status: Active

Product Category: Crimp Terminals Engineering Number: 5556GS3

Packaging Alternative: 39000090 (Bag)



Documents & Resources

Drawings

039000089_sd.pdf 55560001-PK-000.pdf

Specifications

55560001-AS-000.pdf

55560002-AS-000.pdf

AS-58696-004-001.pdf

55560002-PS-CH-000.pdf

55560002-PS-ES-000.pdf

55560002-PS-SK-000.pdf

55560008-TS-000.pdf

PS-5556-001-001.pdf

PS-5556-002-001.pdf

PS-58691-004-001.pdf

55560001-TS-000.pdf

55560010-TS-000.pdf

TS-5556-002-001.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Compliant with Exemption 34; 33; |
|--------------------|----------------------------------|
| China RoHS | © |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |

| REACH SVHC | Not Contained per D(2024)7663-DC (21 Jan 2025) |
|------------|---|
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|--------------|---|
| Category | Crimp Terminals |
| Series | 5556 |
| Description | Mini-Fit Female Crimp Terminal, Gold (Au) over Brass, 16 AWG, Reel |
| Application | Power, Wire-to-Board, Wire-to-Wire |
| Product Name | Mini-Fit |
| UPC | 800754394895 |

Electrical

| Current - Maximum per Contact | 9.0A |
|-------------------------------|------|
| Voltage - Maximum | 600V |

Physical

| Durability (mating cycles max) | 30 |
|--------------------------------|--------|
| Gender | Female |
| Material - Metal | Brass |
| Material - Plating Mating | Gold |
| Material - Plating Termination | Tin |

| Net Weight | 228.000/mg |
|-----------------------------|----------------------|
| Packaging Type | Reel |
| Plating min - Mating | 0.762µm |
| Plating min - Termination | 0.762µm |
| Termination Interface Style | Crimp or Compression |
| Wire Insulation Diameter | 1.80-3.10mm |
| Wire Size (AWG) | 16 |
| Wire Size mm ² | N/A |

Solder Process Data

| Lead-Free Process Capability | N/A |
|------------------------------|-----|
|------------------------------|-----|

Use with Part(s)

| Description | Part Number |
|--|--------------|
| Mini-Fit Jr. Receptacle Housings | <u>5557</u> |
| Mini-Fit BMI Dual Row Receptacle Housings | <u>44516</u> |
| Mini-Fit BMI Dual Row Receptacle Housings | 42474 |
| Mini-Fit BMI Dual Row Receptacle Housings | 43760 |
| Mini-Fit Jr. Dual Row Receptacle Housings | <u>46992</u> |

Application Tooling

Global

| Description | Part Number |
|--|-----------------|
| Extraction Tool for Mini-Fit Jr. Terminals | <u>11030044</u> |
| Hand Crimp Tool for Mini-Fit Jr. Male and Female Crimp Terminals, 16 AWG | 2002182200 |
| FineAdjust Applicator for Insulation OD 2.20-2.45mm, 16 AWG | 639039400 |
| FineAdjust Applicator for Insulation OD 2.60-3.15mm, 16 AWG | 639041400 |
| FineAdjust Applicator for Insulation OD 1.80-2.20mm, 16 AWG | 639041500 |

| FineAdjust Crimp Applicator for Mini-Fit Crimp Terminals, 22+20, 20+20 and 22+18 AWG, UL 1007 Wires Only | 2037022100 |
|---|------------|
| FineAdjust Crimp Applicator for Mini-Fit Crimp Terminals, 22+20, 20+20 and 22+18 AWG, UL 1061 Wires Only | 2037022200 |

This document was generated on Apr 24, 2025