

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

LOC  
J

DIST

REVISIONS  
変更

P

LTR

DESCRIPTION

DATE

DWN

APVD

E

REVISED PER-ECR-20-011859

21AUG2020

M. J

E. I

2.5

2.5Xn=A

CAVITY MARK  
(ALPHABET:CAPITAL LETTER)

3.3

01 6 8 3 2 1

CIRCUIT NO

COMPANY LOGO

SERIES CODE

KEYING: X

D

C

B

A

12.45

ROW ID

11.3

8.6

9.4

9

2.5

2.5Xn=A

3.3

20POS(X-KEY): 1-1827864-0

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:  
単位: 耗  
mm

TOLERANCES UNLESS  
OTHERWISE SPECIFIED:

一般公差 ±0.3, ±5°

0-PLC ±

1-PLC ±

2-PLC ±

3-PLC ±

4-PLC ±

ANGLES ±

FINISH  
仕上

MATERIAL  
材料

1

DWN  
T. KUDO 23AUG2005

CHK  
D. MITSUGI 23AUG2005

APVD  
D. MITSUGI 23AUG2005

PRODUCT SPEC  
製品規格 108-78268, 78298

APPLICATION SPEC  
取付適用規格 114-5377

WEIGHT

CUSTOMER DRAWING

TE Connectivity

DYNAMIC DI200D 2.5mm PITCH  
REC HSG  
4-20 POS

SIZE  
A3

CAGE CODE  
00779

DRAWING NO  
C-1827864

RESTRICTED TO

SCALE  
尺度 4:1

SHEET  
1

OF  
4

REV  
E

1. MATERIAL: GLASS FILLED THERMO PLASTIC  
POLYESTER(94V-0), COLOR: BLACK

2. THE SHAPE, SIZE AND POSITION  
OF THE CHARACTER SHOW THE OUTLINE.  
THEY DON'T SHOW DETAILS.

3. THE KEYING ARRANGEMENT OF "Y" IS  
SYMMETRIC WITH "X".

4. DIFFERENT HEIGHT OF LOCK PROTECTOR.  
A FINGERTIP IS STOOD AND PUSHED  
WHEN OPERATING A LOCK LEVER.

1. 材料: ガラス入り熱可塑性ポリエステル樹脂(94V-0), 色: 黒

2. 文字の形状、大きさ、および位置については、大略を示すものであり、  
詳細を示すものではありません。

3. Y KEY形状は、X KEY形状と左右対称

4. LOCK PROTECTORの高さ違いです。  
ロックレバー操作の際には、指先を立てて押してください。

|     |     |   |      |      |      |     |             |
|-----|-----|---|------|------|------|-----|-------------|
| 20  | Y   | 9 | 22.5 | 25.9 | 27.6 | 8.3 | 2-1827864-0 |
| 20  | X   | 9 | 22.5 | 25.9 | 27.6 | 8.3 | 1-1827864-0 |
| 16  | Y   | 7 | 17.5 | 20.9 | 22.6 | 8.3 | 2-1827864-8 |
| 16  | X   | 7 | 17.5 | 20.9 | 22.6 | 8.3 | 1-1827864-8 |
| 12  | Y   | 5 | 12.5 | 15.9 | 17.6 | 8.3 | 2-1827864-6 |
| 12  | X   | 5 | 12.5 | 15.9 | 17.6 | 8.3 | 1-1827864-6 |
| 12  | X   | 5 | 12.5 | 15.9 | 17.6 | 8.3 | 9-1827864-6 |
| 10  | Y   | 4 | 10.0 | 13.4 | 15.1 | 3.3 | 2-1827864-5 |
| 10  | X   | 4 | 10.0 | 13.4 | 15.1 | 3.3 | 1-1827864-5 |
| 8   | Y   | 3 | 7.5  | 10.9 | 12.6 | 3.3 | 2-1827864-4 |
| 8   | X   | 3 | 7.5  | 10.9 | 12.6 | 3.3 | 1-1827864-4 |
| 6   | Y   | 2 | 5.0  | 8.4  | 10.1 | 3.3 | 2-1827864-3 |
| 6   | X   | 2 | 5.0  | 8.4  | 10.1 | 3.3 | 1-1827864-3 |
| 6   | X   | 2 | 5.0  | 8.4  | 10.1 | 3.3 | 9-1827864-3 |
| 4   | Y   | 1 | 2.5  | 5.9  | 7.6  | 3.1 | 2-1827864-2 |
| 4   | X   | 1 | 2.5  | 5.9  | 7.6  | 3.1 | 1-1827864-2 |
| 4   | X   | 1 | 2.5  | 5.9  | 7.6  | 3.1 | 9-1827864-2 |
| POS | KEY | n | A    | B    | C    | D   | PART NO     |

1470-19 (3/11)

THIS DRAWING IS UNPUBLISHED.


RELEASED FOR PUBLICATION

© COPYRIGHT -

ALL RIGHTS RESERVED.

| LOC | DIST | REVISIONS |     |             |    | DATE | DWN | APVD |
|-----|------|-----------|-----|-------------|----|------|-----|------|
|     |      | P         | LTR | DESCRIPTION | 変更 |      |     |      |
| J   |      | -         | -   | SEE SHEET 1 |    | -    | -   | -    |

CAVITY MARK  
ONLY 4POS



4POS(X-KEY)  
1-1827864-2

6POS(X-KEY)  
1-1827864-3


8POS(X-KEY)  
1-1827864-4

10POS(X-KEY): 1-1827864-5 12POS(X-KEY): 1-1827864-6

4 12POS(X-KEY): 9-1827864-6

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:  
単位: 耗  
mm



MATERIAL  
材料

TOLERANCES UNLESS  
OTHERWISE SPECIFIED:

一般公差  
0 PLC ±  
1 PLC ±  
2 PLC ±  
3 PLC ±  
4 PLC ±  
ANGLES ±

FINISH  
仕上

DWN 23AUG2005

T. KUDO

CHK 23AUG2005

D. MITSUGI

APVD 23AUG2005

D. MITSUGI

PRODUCT SPEC

製品規格

108-78268,78298

APPLICATION SPEC

取付適用規格

114-5377

WEIGHT

CUSTOMER DRAWING



TE Connectivity

NAME  
名称 DYNAMIC DI200D 2.5mm PITCH  
REC HSG  
4-20 POS

SIZE

CAGE CODE

DRAWING NO

番号

A3

00779

C

1827864

RESTRICTED TO

SCALE

尺度

4:1

SHEET

2

OF

4

REV

E

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT -

ALL RIGHTS RESERVED.

LOC  
J

DIST

REVISIONS  
変更

P

LTR





DESCRIPTION

DATE




DWN

APVD

SEE SHEET 1




16POS(X-KEY): 1-1827864-8



6POS(X-KEY): 9-1827864-3

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:  
単位: 耗  
mm



MATERIAL  
材料

TOLERANCES UNLESS  
OTHERWISE SPECIFIED:

一般公差

0 PLC

1 PLC

2 PLC

3 PLC

4 PLC

ANGLES

FINISH  
仕上

±

±

±

±

±

±

±

DWN T. KUDO 23AUG2005

CHK D. MITSUGI 23AUG2005

APVD D. MITSUGI 23AUG2005

PRODUCT SPEC

製品規格

108-78268, 78298

APPLICATION SPEC

取付適用規格

114-5377

WEIGHT

CUSTOMER DRAWING



TE Connectivity

NAME  
名称  
DYNAMIC D1200D 2.5mm PITCH  
REC HSG  
4-20 POS

SIZE

CAGE CODE

DRAWING NO

番号

A3

00779

C

1827864

RESTRICTED TO

SCALE

尺度

4:1

SHEET






3

OF

4

REV

E



4 4POS(X-KEY):9-1827864-2

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:  
単位: 耗  
mm

MATERIAL  
材料

TOLERANCES UNLESS  
OTHERWISE SPECIFIED:

一般公差

0 PLC ±

1 PLC ±

2 PLC ±

3 PLC ±

4 PLC ±

ANGLES ±

FINISH  
仕上

DWN  
T. KUDO 23AUG2005

CHK  
D. MITSUGI 23AUG2005

APVD  
D. MITSUGI 23AUG2005

PRODUCT SPEC  
製品規格  
108-78268, 78298

APPLICATION SPEC  
取付適用規格  
114-5377

WEIGHT

CUSTOMER DRAWING

TE Connectivity

NAME  
名称  
DYNAMIC D1200D 2.5mm PITCH  
REC HSG  
4-20 POS

SIZE  
A3

CAGE CODE  
00779

DRAWING NO  
番号  
C-1827864

RESTRICTED TO

SCALE  
尺度  
4:1

SHEET  
4

OF  
4

REV  
E

1470-19 (3/11)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2-1827864-5](#)