

Sep.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

1		2			3			4		
COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	
△				. .	△				. .	
△				. .	△				. .	
△				. .	△				. .	

8+0.05
-0.15 HEX

HRM (SMA)

1/4-36UNS-2A

4.62±0.02

7±0.2

13.55±0.3

(3.7)

1.9 0/-0.05

ML51

5 PRESS FITTING

4

3

1

2

3	BERYLLIUM COPPER	GOLD PLATING			
2	PTFE		5	STAINLESS STEEL	PASSIVATE
1	STAINLESS STEEL	NICKEL PLATING	4	PTFE	
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
CODE NO. (OLD) CL399-2837-5			DRAWN <i>J. Matsumoto</i> 99.6.29		
			DESIGNED <i>J. Matsumoto</i> 99.6.29		
			CHECKED <i>K. Shimizu</i> 99.6.29		
			APPROVED <i>J. Matsumoto</i> 99.6.30		
			RELEASED		

TO

RF

SCALE
5 : 1

UNITS
mm

DRAWING NO.
EDC4-134871

HRS HIROSE ELECTRIC CO., LTD.

PART NO.
HRM.J-ML51.J-A

CODE NO.
CL311-0316-2

1/1

FORM NO. 22

RF