





P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	ECN-23-233700TE STANDARD	05OCT2023	KS	RB



ISO 1:1

NOTES
Bemerkungen

- 1 TE-CONNECTIVITY ORDER-NUMBER
TE-Connectivity Bestellnummer
- 2 HOLE FOR PIN (TO SECURE GUARD)
Plombierloch
- 3 EYELET FOR PIN
Plombieröse
- 4 FOR THREADS M12
Für Gewinde M12

5 ENVIRONMENTAL TEMPERATURE
OPERATING RANGE FROM -35°C TO +60°C
STORAGE -35°C TO +80°C
Temperaturverhalten
Die Sicherheitsklappe ist im Bereich von -35°C bis +60°C voll funktionstüchtig.
Die Lagertemperatur liegt zwischen -35°C und +80°C.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN K.Kullick	10APR2000
		CHK K.Kullick	10APR2000
		APVD K.Kullick	10APR2000
		PRODUCT SPEC	
		APPLICATION SPEC	
		WEIGHT	
		CUSTOMER DRAWING	
DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED: DIN ISO 2768 cL		
	0 PLC	±	
	1 PLC	±	
	2 PLC	±	
	3 PLC	±	
	4 PLC	±	
	ANGLES	±	
	FINISH		
MATERIAL			

K1022530	1	A	SWITCH GUARD Sicherheitsklappe	11	1
TE ORDER-NO.	REV.	DESCRIPTION	WEIGHT [g]	ITEM NO.	

PARTS LIST



TE Connectivity

NAME
SWITCH GUARD
Sicherheitsklappe

SIZE A3	CAGE CODE 00779	DRAWING NO C-07-0-0-01	RESTRICTED TO -
------------	--------------------	---------------------------	--------------------

SCALE 2:1	SHEET 1 OF 1	REV A
--------------	-----------------	----------