


Aug.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


<Cable soldering tool>

- Jig for soldering of center contact : MMCX(AR)-P-SF/SO-MD1
- Jig for soldering of outer contact : MMCX(AR)-P-SF/SO-MD2



【 USAGE PRECAUTIONS OF MMCX(AR) 】

1. Insertion or extraction a plug of MMCX(AR) as perpendicularly as possible with aligning the plug with a receptacle. When aligned insertion or extraction is not performed, it would damage or deform an outer conductor part.
2. Do not apply excess load on soldered section with cable



3	PHOSPHOR BRONZE	GOLD PLATING							
2	PTFE			5	BRASS	GOLD PLATING			
1	BRASS	GOLD PLATING		4	BERYLLIUM COPPER	GOLD PLATING			
NO.	MATERIAL	FINISH	REMARKS	NO.	MATERIAL	FINISH	REMARKS		
UNITS mm		SCALE 5 : 1	COUNT 	DESCRIPTION OF REVISIONS			DESIGNED	CHECKED	DATE
HIROSE ELECTRIC CO., LTD.		APPROVED	·KY. SHIMIZU	16.07.25	DRAWING NO.	EDC-364476-00-00			
		CHECKED	·KY. SHIMIZU	16.07.25	PART NO.	MMCX(AR)-P-SF047			
		DESIGNED	·TM. YOSHIDA	16.07.25	CODE NO.	CL339-0032-0-00			
		DRAWN	·TM. YOSHIDA	16.07.25					